GORTEF HIGH PERFORMANCE PTFE

PRODUCT SPECIFICATION

TCG010AD



Product	Product category	Coating
PTFE GLASS FABRIC SELF ADHESIVE	INDUSTRIAL SERIE	SILICONE PSA

Gortef Industrial Series PTFE/glass fabrics coated on one side with high temperature pressure sensitive silicone adhesive. Yellow textured PVC release liner is applied to the adhesive surface for ease of application.

Some application: Easy release surface on heat sealing and packaging machines, ironing and pressing equipment, covering drying cylinders, lining chutes, release surface on bonding tools.

Properties	Value	Unit
Standart width(s) Please ask for other widths	1000, 1500	mm
Backing thickness	0,22	mm
Total thickness	0,27	mm
Backing weight	455	gr/m²
Adhesion	6,00	N/cm
Temperature resistance	-73 / +260	°C

Note: Nominal thickness, weight and adhesion values are typical and are not intended as a specification minimum.

Weight Tolerance $g/m^2 = \pm \%5$

All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained here in are based on test results GORTEF believes to be reliable, but they are not to be constured in any manner as warranties expressed.

All data is subject to change without notice.



GORTEF HIGH PERFORMANCE PTFE

UNIT 35, LEVEL 2, 42-46 Wattle Road, Brookvale, Sydney, NSW, Australia ,2100. TEL : +61 2 9938 4493 FAX : +61 2 9938 4496 www.gortef.com info@gortef.com